

# LD SERIES

## LD1.0/2.0/3.0

Simple loop driver  
Class D Amplifier



LDx.2 amplifiers from Opus Technologies are next generation induction loop Class-D amplifiers. The two channels amplifiers offer all the functionalities (AGC, MLC, compressor, etc) to ensure room installations up to 2x250m<sup>2</sup> (LD1.2), 2x450<sup>2</sup> (LD2.2) or 2x1000m<sup>2</sup> (LD2.3).

It can equip adjoining rooms (amphitheater, courtroom, etc.) with two magnetic loops installed hairpin or the areas with a metal. This type of installation makes it possible to limit the external radiation of the magnetic field, to guarantee uniformity of coverage and to provide a power which makes it possible to limit the distortions due to the presence of metal.

The LDx.2 series can also be used to equip large areas such as fairgrounds or stadium stands.

Thanks to high frequency switching mode proprietary solutions, the amplifiers are one of the most compact on the market and do not need any active cooling. They include a LEDs indicator fault synthesis on the driver's front panel to control the integrity of both loop and amplifier. Informations can be deported thanks to a dry contact relay.

The high-grade power supply and output voltage capability (48Vpk) ensure outstanding sound quality with high dynamic and extremely low distortion.

Amplifiers have been developed with strict and rigorous specifications that allow us to offer a 5 year warranty and meet the IEC 60118-4. LD1.0, LD2.0,

LD3.0 amplifiers follow strict specifications required for UL compliance.

- ✓ Two channels amplifier
- ✓ High frequency switching proprietary mode
- ✓ Efficiency up to 92%
- ✓ Natural cooling
- ✓ AGC: Automatic Gain Control optimized for speech
- ✓ 3 inputs with selectable gain
- ✓ 70/100V priority alarm input
- ✓ Phantom supply for microphone
- ✓ Slave amplifier input and output
- ✓ Adjustable metal losses correction
- ✓ 1U wall mounting available
- ✓ Compact and light
- ✓ 5-Year warranty
- ✓ LEDs indicator
- ✓ Relay fault synthesis
- ✓ IEC 62368/UL compliant
- ✓ Over current, over temperature and short circuit protections



### Coverage

Cover meets the IEC 60118-4 standard

Loop	No metal loss			Moderate metal loss			High metal loss		
	Perimeter loop	Single array in 8	Low overspill*	Perimeter loop	Single array in 8	Low overspill*	Perimeter loop	Single array	Low overspill*
LD1.2	250m <sup>2</sup> (10x25m)	450m <sup>2</sup> (15x30m)	450m <sup>2</sup> (15x30m)	130m <sup>2</sup> (10x13m)	180m <sup>2</sup> (10x18m)	450m <sup>2</sup> (15x30m)	Use Multi Loop Systems LDx.2 and/or Contact us		
LD2.2	450m <sup>2</sup> (15x30m)	650m <sup>2</sup> (20x32,5m)	650m <sup>2</sup> (20x32,5m)	160m <sup>2</sup> (10x16m)	280m <sup>2</sup> (8x35m)	650m <sup>2</sup> (20x32,5m)			
LD3.2	1 000m <sup>2</sup> (16x62m)	1 400m <sup>2</sup> (35x40m)	1 400m <sup>2</sup> (35x40m)	250m <sup>2</sup> (10x25m)	360m <sup>2</sup> (10x36m)	1 400m <sup>2</sup> (35x40m)			

\*with 2 amplifiers

# LD SERIES

## LD1.0/2.0/3.0

Simple loop driver  
Class D Amplifier



Coverage surface	LD1.2	LD2.2	LD3.2
Single loop	300 m <sup>2</sup> (10x30m <sup>2</sup> )	525m <sup>2</sup> (15x35 m <sup>2</sup> )	800m <sup>2</sup> (20x50m <sup>2</sup> )
Multiloop	600 m <sup>2</sup> (15x40m <sup>2</sup> )	1200 m <sup>2</sup> (20x60 m <sup>2</sup> )	2000 m <sup>2</sup> (20x80m <sup>2</sup> )
<b>Power input</b>			
Voltage	100-240Vac, 50-60Hz	100-240Vac, 50-60Hz	100-240Vac, 50-60Hz
Consumption at idle with 1Ω loop connected	14W at 230Vac and 25°C ambient temperature	14W at 230Vac and 25°C ambient temperature	14W at 230Vac and 25°C ambient temperature
Nominal power consumption at 1Ω	80W	100W	180W
Maximum power consumption	<500 VA	<600 VA	<700 VA
Connector	IEC C13	IEC C13	IEC C13
<b>Audio input</b>			
Input channels with separated adjustable gain	Input 1: 70/100V signal (priority signal) Input 2: Microphone or line Input 3: Microphone or line	Input 1: 70/100V signal (priority signal) Input 2: Microphone or line Input 3: Microphone or line	Input 1: 70/100V signal (priority signal) Input 2: Microphone or line Input 3: Microphone or line
Phantom supply	Available on microphone inputs: 12V,2 mA	Available on microphone inputs: 12V, 2 mA	Available on microphone inputs: 12V, 2 mA
Sensitivity	- Microphone: -50 dB - Line: -10 dB - 100V: +40 dB	- Microphone: -50 dB - Line: -10 dB - 100V: +40 dB	- Microphone: -50 dB - Line: -10 dB - 100V: +40 dB
Connector	MTSB terminal block and/or Combo Neutrik for input 3	MTSB terminal block and/or Combo Neutrik for input 3	MTSB terminal block and/or Combo Neutrik for input 3
<b>Audio output</b>			
Loop impedance	0.5 Ω to 3 Ω	0.5 Ω to 3 Ω	0.5 Ω to 3 Ω
Max output current	2x5 Arms, 2x7 Apeak	2x7.5 Arms, 2x10Apeak	2x10 Arms, 2x14Apeak
Max output voltage	34 Vrms, 48 Vpeak	34 Vrms, 48 Vpeak	34 Vrms, 48 Vpeak
THD	< 0.5% at nominal output current, 1 Ω loop, 1kHz	< 0.5% at nominal output current, 1 Ω loop, 1kHz	< 0.5% at nominal output current, 1 Ω loop, 1kHz
Bandwidth	80 Hz to 9.5 kHz, -3 dB	80 Hz to 9.5 kHz, -3 dB	80 Hz to 9.5 kHz, -3 dB



	LD1.2	LD2.2	LD3.2
<b>Audio output</b>			
<b>Dynamic</b>	>36 dB	>36 dB	>36 dB
<b>Metal loss correction</b>	0 to 3dB per octave filter	0 to 3dB per octave filter	0 to 3dB per octave filter
<b>Connector</b>	MTSBA terminal block	MTSBA terminal block	MTSBA terminal block
<b>Slave Amplifier</b>			
<b>Input / outputs</b>	One of each	One of each	One of each
<b>Connectors</b>	Jack 6.35 mm	Jack 6.35 mm	Jack 6.35 mm
<b>LEDs indicator</b>			
<b>« Power »</b>	Switched on when module powered	Switched on when module powered	Switched on when module powered
<b>« Protect »</b>	Switched on when signal clipping, too high temperature reached or in case of loop failure		
<b>« Loop »</b>	Switched on when the loop is in working conditions	Switched on when the loop is in working conditions	Switched on when the loop is in working conditions
<b>Vu meters « Input »</b>	Input signal level after adjustment	Input signal level after adjustment	Input signal level after adjustment
<b>Vu-meters « output »</b>	Percentage of maximum current drawn	Percentage of maximum current drawn	Percentage of maximum current drawn
<b>NO/NC fault relay synthesis (contact closed once one fault is detected)</b>			
<b>Detected faults</b>	Too high temperature raised and loop failure	Too high temperature raised and loop failure	Too high temperature raised and loop failure
<b>Maximum electrical rating</b>	0.5A/125Vac or 1A/24Vdc	0.5A/125Vac or 1A/24Vdc	0.5A/125Vac or 1A/24Vdc
<b>Connector</b>	MTSB terminal block	MTSB terminal block	MTSB terminal block
<b>General</b>			
<b>Protections</b>	Over current, over temperature, short circuit	Over current, over temperature, short circuit	Over current, over temperature, short circuit
<b>Operating temperature</b>	0 to + 45°C	0 to + 45°C	0 to + 45°C
<b>Storage temperature</b>	-30 to +70°C	-30 to +70°C	-30 to +70°C
<b>Size</b>	42x200x215 mm / 1.6x7.9x8.5 inch	42x200x215 mm / 1.6x7.9x8.5 inch	42x200x215 mm / 1.6x7.9x8.5 inch
<b>Weight</b>	1,56kg / 3,43lbs	1,56kg / 3,43lbs	1,56kg / 3,43lbs